

HARVESTER SPECIAL - Spécifications techniques



Description

HARVESTER SPECIAL a été spécialement conçu pour les moissonneuses. Les crampons à double angle assurent une excellente traction aux champs et un confort de conduite extraordinaire sur route. Le dessin spécial de la bande de roulement offre un contact plus large pour une stabilité exceptionnelle. HARVESTER SPECIAL se distingue de par la carcasse robuste et par un mélange particulièrement résistant aux coupures et déchirures, assurant un cycle de vie du pneu plus long.

UM

International Standard

Construction

❖ BIAS

Machinery

Agriculture: Moissonneuse

Version	DUAL BEAD
Type	TL
Tyre Size	23.5 - 25
LI/SS	191 A2

Dimensions International Standard

Ply Rating	20
Section Width (mm)	615
Overall Diameter (mm)	1665
Static Loaded Radius (mm)	715
Rolling Circumference (mm)	5058
Rim Rec	19.50/2.5
ECE	E11-106R-006954
TRA Code	R1

Load capacity (Kg)

km/h / bar	3.75
10	10900

Printed on 09/05/2024 04:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..