

I - 1 - Spécifications techniques



Description

I-1 a été conçu pour le transport aux champs et sur route ainsi que pour les opérations de travail du terrain avec des outils agricoles et des remorques. I-1 est un pneu à haute vitesse qui optimise les temps de transfert, afin que vous puissiez vous concentrer sur votre activité principale. Le dessin spécifique de la bande de roulement assure un long cycle de vie du pneu, même dans les conditions pénibles et en présence de chaumes dans les champs.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Remorque

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 12.5L - 15 SL |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94005994 |
| Ply Rating | 10 |
| Section Width (inch) | 12.2 |
| Overall Diameter (inch) | 32.3 |
| Static Loaded Radius (inch) | 14.3 |
| Rolling Circumference (inch) | 94.6 |
| Rim Rec | 10 LB |
| ECE | E11-106R-004578 |
| TRA Code | I1 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 44 |
| 40 | 3420 |

Printed on 08/12/2023 04:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..