

## INDUSTRIAL RIB F3 - Spécifications techniques



### Description

INDUSTRIAL RIB F3 est un pneu agro-industriel avec dessin à blocs de la bande de roulement conçu pour le transport aux champs et sur route ainsi que pour les travaux des champs avec outils agricoles et remorques. Ce pneu se distingue de par son mélange extrêmement résistant aux chaumes qui le rend idéal pour les conditions de fonctionnement les plus critiques, et lui assure un long cycle de vie.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	11L - 15 SL
LI/SS	117 A6

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	279
Overall Diameter (mm)	813
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-004303
TRA Code	F3

## Load capacity (Kg)

km/h / bar	4.20
30	1290
40	1160

Printed on 27/04/2024 04:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..