

IT 400 - Spécifications techniques



Description

IT 400 est un pneu avec dessin à blocs de la bande de roulement qui convient pour une utilisation essentiellement de transport sur route pour les remorques à plateau surbaissé. Ce pneu est adapté pour les applications à haute vitesse et permet de réaliser d'importantes économies de carburant.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Remorque surbaissé

Version	STANDARD
Type	TL
Tyre Size	8.25 - 15
LI/SS	129/125 J

Dimensions US Standard

Usa code	94031818
Ply Rating	14
Section Width (inch)	9.4
Overall Diameter (inch)	33.3
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	98.9
Rim Rec	6.50
Rim Alt	6.0 ; 7.0
ECE	E11-54R-0018586

Load capacity (lbs)

mph / psi	125	115	105
10	6525	-	-
20	-	5380	-
62 LS	-	4080	-
62 LD	-	-	3640

Printed on 28/04/2024 03:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..