

LG 306 - Spécifications techniques



Description

LG 306 est un pneu pour pelouses et jardins, approprié pour les faucheuses. Dans certaines tailles, LG 306 convient aussi pour les micro tracteurs. Le dessin spécifique de la bande de roulement rend le pneu délicat sur le terrain, tout en facilitant le maniement et les manœuvres. LG 306 est disponible dans une version "aramid-belted", avec ceintures en aramide, pour les utilisateurs qui ont besoin d'une plus grande résistance aux perforations.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Faucheuse • Micro tracteur

| | |
|-----------|-----------------|
| Version | ARAMID BELTED |
| Type | TL |
| Tyre Size | 29 X 12.50 - 15 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94062782 |
| Ply Rating | 10 |
| Section Width (inch) | 12.5 |
| Overall Diameter (inch) | 29.1 |
| Static Loaded Radius (inch) | 13.7 |
| Rolling Circumference (inch) | 87.8 |
| Rim Rec | 10 LB |
| ECE | E11-106R-006167 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 60 |
| 30 | 2535 |

Printed on 20/04/2024 09:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..