

LG 307 - Spécifications techniques



Description

LG 307 est un pneu pour pelouses et jardins, approprié pour les faucheuses. Le dessin spécifique de la bande de roulement rend le pneu délicat sur le terrain, pour éviter d'abîmer la pelouse et faciliter le maniement et les manœuvres.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Faucheuse

Version	STANDARD
Type	TL
Tyre Size	20 X 10.00 - 8

Dimensions International Standard

Ply Rating	4
Section Width (mm)	255
Overall Diameter (mm)	495
Static Loaded Radius (mm)	215
Rolling Circumference (mm)	1435
Rim Rec	8.00 I - 55 ; I - 70 ; I - 90
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005200

Load capacity (Kg)

km/h / bar	1.50
15	545

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 08:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..