

LG 307 - Fiche de données



Description

LG 307 est un pneu pour pelouses et jardins, approprié pour les faucheuses. Le dessin spécifique de la bande de roulement rend le pneu délicat sur le terrain, pour éviter d'abîmer la pelouse et faciliter le maniement et les manœuvres.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Faucheuse

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
20 X 10.00 - 8	STANDARD	4	8.00 I - 55 ; I - 70 ; I - 90	7.00 I - 55 ; I - 70 ; I - 90	255	495	215	1435	TL	E11-106R-005200
20 X 10.00 - 8	STANDARD	6	8.00 I - 55 ; I - 70 ; I - 90	7.00 I - 55 ; I - 70 ; I - 90	255	495	215	1435	TL	E11-106R-003462
20 X 12.00 - 10	STANDARD	4	8.5 I - 55 ; I - 70 ; I - 90		285	500	221	1435	TL	E11-106R-003463

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 06:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..