

## LG RIB PLUS - Spécifications techniques



### Description

Le LG RIB PLUS est un pneu pour pelouse et jardin qui convient aux tondeuses, aux petits tracteurs et aux faneuses.

Sa bande de roulement a été spécialement conçue pour que le pneu roule doucement sur le sol, ce qui évite d'endommager le gazon, tout en facilitant la manipulation.

Le profil rond permet au LG RIB PLUS de prendre en douceur les virages sur le terrain.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Faucheuse • Micro tracteur

Version	STANDARD
Type	TL
Tyre Size	16 X 6.50 - 8

## Dimensions International Standard

<b>Ply Rating</b>	10
<b>Section Width (mm)</b>	170
<b>Overall Diameter (mm)</b>	408
<b>Rim Rec</b>	5.375 I - 55 ; I - 70 ; I - 90

## Load capacity (Kg)

km/h / bar	4.90
15	480

Printed on 23/04/2024 23:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..