

LIFT STAR PLUS - Spécifications techniques



Description

LIFT STAR PLUS est un pneu diagonal particulièrement conçu pour les chargeuses télescopiques utilisées pour les opérations pénibles dans le secteur du bâtiment et dans d'autres applications difficiles. Le profil bas du flanc offre une excellente stabilité lors des opérations de levage en hauteur, tandis que le dessin non directionnel de la bande de roulement permet une plus grande polyvalence lors du montage. De plus, le flanc a été particulièrement conçu pour assurer une résistance encore plus grande aux coupures et lacérations.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	400/75 - 28

Dimensions US Standard

Usa code	94046225
Ply Rating	16
Section Width (inch)	15.7
Overall Diameter (inch)	51.9
Static Loaded Radius (inch)	23.3
Rolling Circumference (inch)	155.3
Rim Rec	12.00 GR
ECE	E11-106R-005330

Load capacity (lbs)

mph / psi	51	73
30	8545	-
5	-	13890

Printed on 24/04/2024 05:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..