

## LOADER SPECIAL - Spécifications techniques



### Description

LOADER SPECIAL L-5 est un pneu à structure diagonale qui garde vos chargeuses en mouvement en leur assurant une excellente efficacité dans les opérations pénibles sur les terrains rocheux. L'excellente traction et la résistance exceptionnelle aux coupures vous aideront à améliorer votre productivité.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Bulldozer • Chargeur

Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

## Dimensions US Standard

Usa code	94069958
Ply Rating	20
Overall Width (inch)	20.9
Overall Diameter (inch)	61.8
Rim Rec	17.00/2.0
TRA Code	L5

## Load capacity (lbs)

mph / psi	65
5	20900

Printed on 23/04/2024 15:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..