

LT TR 182 - Fiche de données



Description

LT TR 182 convient pour les opérations de transports avec véhicules utilitaires légers. Ce pneu à haute vitesse est utilisé essentiellement sur route et il réduit considérablement la consommation de carburant. De plus, le pneu LT TR 182 est facile à monter.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Camion léger

| SIZE | Version | USACode | PR | RIM REC | RIM ALT | SW | OD | Type |
|----------|----------|----------|----|---------|---------|-----|----|------|
| 8 - 14.5 | STANDARD | 94027910 | 12 | 6.00 MH | | 8.1 | 28 | TL |
| 8 - 14.5 | STANDARD | 94027927 | 14 | 6.00 MH | | 8.1 | 28 | TL |

Printed on 20/04/2024 08:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..