

## MAGLIFT ECO RIB - Spécifications techniques



### Description

MAGLIFT ECO RIB a été particulièrement conçu pour les remorques de matériels au sol pour aéronefs. Sa structure renforcée élimine tout risque de dérapage, tandis que le bord de protection particulier de la jante protège le pneu contre dommage. MAGLIFT ECO RIB assure un contrôle de la direction exceptionnelle, une stabilité excellente, un faible niveau de vibrations ainsi que l'auto-ement de la remorque. Les autres avantages sont une faible résistance au roulement et un développement réduit de la chaleur pour une efficacité améliorée.

### UM

US Standard

### Construction

◆ SOLID

### Machinery

Industriel: Chariot élévateur

Version	STANDARD
---------	----------

Type	
------	--

Tyre Size	4.00 - 8
-----------	----------

## Dimensions US Standard

Usa code	94062706
Section Width (inch)	4.9
Overall Diameter (inch)	16.1
Rim Rec	3.75 I - 8

## Load capacity (lbs)

mph / psi	-
3 OTHER VEHICLES	2225
5 OTHER VEHICLES	2015
15 OTHER VEHICLES	1710

Printed on 25/04/2024 17:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..