

# MAGLIFT ECO - Spécifications techniques



### Description

MAGLIFT ECO a été particulièrement conçu pour les applications avec chariots élévateurs. Le pneu se distingue de par les rampons larges qui assurent une stabilité maximale et une répartition de la charge optimisée. Sa structure renforcée élimine tout risque de dérapage, tandis que le bord de protection particulier de la jante protège le pneu contre dommage. MAGLIFT ECO assure une excellente traction et une faible résistance au roulement et à la chaleur pour une efficacité améliorée.

### UM

US Standard

### Construction

SOLID

### Machinery

Industriel: Chariot élévateur

Version	STANDARD
Type	
Tyre Size	5.00 - 8

### Dimensions US Standard

Usa code	94061969
Section Width (inch)	4.4
Overall Diameter (inch)	17.9
Rim Rec	3.00 D - 8

### Load capacity (lbs)

mph / psi	
15 LOAD WHEEL	3120
15 STEER WHEEL	2405

Printed on 04/10/2022 11:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..