

## MAGLIFT - Spécifications techniques



### Description

MAGLIFT a été conçu pour toutes les opérations avec chariots élévateurs pour la manutention dans les secteurs industriels et logistique. Ce pneu plein se distingue de par sa capacité de charge élevée et son confort exceptionnel. MAGLIFT offre une excellente résistance aux crevaisons, ce qui se traduit par un cycle de vie plus long du pneu. Sa structure renforcée réduit les risques de dérapage, tandis que la forme particulière de la tringle facilite le montage sur la jante.

### UM

US Standard

### Construction

◆ SOLID

### Machinery

Industriel: Chariot élévateur

Version

LIP - NON MARKING

Type

Tyre Size

16 X 6 - 8  
(150/75 - 8)

## Dimensions US Standard

Usa code	94053438
TMPH	1
Section Width (inch)	5.5
Overall Diameter (inch)	16.6
Rim Rec	4.33 R - 8

## Load capacity (lbs)

	mph / psi	-
15 LOAD WHEEL		3295
15 STEER WHEEL		2535

Printed on 24/04/2024 22:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..