

MH TR 182 - Spécifications techniques



Description

MH TR 182 convient pour les véhicules qui transportent des mobil-homes. Ce pneu à haute vitesse utilisé essentiellement sur route permet de réaliser d'importantes économies de carburant. MH TR 182 assure un long cycle de vie du pneu et des performances élevées toute sa vie durant.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Maison mobile

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

Dimensions US Standard

Usa code	94008605
Ply Rating	14
Section Width (inch)	8.1
Overall Diameter (inch)	28
Rim Rec	6.00 MH

Load capacity (lbs)

mph / psi	110
62	3060

Printed on 27/04/2024 08:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..