

MP 590 - Fiche de données



Description

MP 590 est un pneu agro-industriel pour les opérations de chargement avec les chargeurs télescopiques et les chariots élévateurs. Ce pneu offre une traction et une stabilité excellentes en même temps qu'une durabilité augmentée.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse télescopique

Industriel: Chariot élévateur • Chargeuse télescopique •

Véhicule universel

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 - 22.5 (445/65 - 22.5)	STANDARD	94044191	20	14.0		18.9	46.9	20.9	139.1	TL	E11-106R-004408
18 - 22.5 (445/65 - 22.5)	STANDARD	94014729	16	14.0		18.9	46.9	20.9	139.1	TL	E11-106R-003019

Printed on 28/11/2023 18:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..