

MP 600 - Spécifications techniques



Description

MP 600 est un pneu agro-industriel pour le secteur entretien de la voirie avec les chargeurs télescopiques et les outils agricoles en assurent une expérience de conduite confortable. Ce pneu offre une traction et des qualités d'autonettoyage excellentes en même temps qu'un long cycle de vie.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Chargeuse télescopique
Industriel: Chargeuse télescopique • Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	400/70 - 24 (16.0/70 - 24)

Dimensions US Standard

Usa code	94015320
Ply Rating	14
Section Width (inch)	15.9
Overall Diameter (inch)	46.7
Static Loaded Radius (inch)	21.5
Rolling Circumference (inch)	139
Rim Rec	13 SDC
Rim Alt	12
ECE	E11-106R-003640

Load capacity (lbs)

	mph / psi	51
	25 DW	8050
	30 DW	7830

Printed on 24/04/2024 06:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..