

MT 612 - Spécifications techniques



Description

MT 612 a été conçu pour des utilisations polyvalentes sur route et hors route. La carcasse robuste permet le transport de charges lourdes à une vitesse élevée, alors que les crampons larges assurent une traction exceptionnelle. La bande de roulement extra large garantit d'excellentes propriétés de flottaisons sur sable et boue.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

Industriel: Véhicule universel

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

Dimensions US Standard

Usa code	94029433
Ply Rating	20
Section Width (inch)	15.4
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	150.7
Rim Rec	10
ECE	E11-54R-0021125

Load capacity (lbs)

mph / psi	110
50 LS	10750
50 LD	9640

Printed on 24/04/2024 07:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..