

MULTIMAX MP 513 - Spécifications techniques



Description

MULTIMAX MP 513 a été conçu par BKT pour les véhicules polyvalents dans le cadre des services municipaux de voirie et de transport pour les applications agricoles et industrielles. Grâce à sa carcasse robuste en nylon renforcée avec des ceintures d'acier, MULTIMAX MP 513 permet de transporter des charges lourdes à de grandes vitesses en assurant une expérience de conduite confortable. Il garantit une vie opérationnelle plus longue, une traction excellente ainsi que des propriétés d'autonettoyage exceptionnelles. Il est idéal pour les véhicules universels et les camions d'engrais.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule universel • Camion d'engrais
Industriel: Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	495/70 R 24 MPT
LI/SS	155 G

Dimensions US Standard

Usa code	94035908
Section Width (inch)	19.6
Overall Diameter (inch)	51.3
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	156.5
Rim Rec	W 16 L
Rim Alt	DW 15 L ; DW 16 L ; W 15 L
ECE	E4-54R-0029057

Load capacity (lbs)

mph / psi	23	29	36	44	51
55	4360	5160	6260	7160	8550
40	4740	5600	6800	7780	9270
25	5030	5940	7210	8240	9830

Printed on 11/12/2023 07:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..