

## MULTIMAX MP 519 - Spécifications techniques



### Description

MULTIMAX MP 519 est un pneu particulièrement conçu pour les camions légers dans toutes les applications de transport. La carcasse renforcée avec ceintures d'acier garantit une excellente stabilité et une vitesse élevée (90 km/h). Grâce à la faible résistance au roulement, le pneu assure une consommation réduite de carburant.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industriel: Camion léger

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 7.50 R 16 LT |
| LI/SS     | 109/107 G    |

## Dimensions US Standard

|                              |                    |
|------------------------------|--------------------|
| Usa code                     | 94053384           |
| Ply Rating                   | 6                  |
| Section Width (inch)         | 8.7                |
| Overall Diameter (inch)      | 31.9               |
| Static Loaded Radius (inch)  | 14.8               |
| Rolling Circumference (inch) | 96.4               |
| Rim Rec                      | 6.00               |
| Rim Alt                      | 5.50 F ; 6 L ; 7 L |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 51   |
| 55 LS     | 2270 |
| 55 LD     | 2150 |

Printed on 19/04/2024 04:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..