

MULTIMAX MP 519 - Fiche de données



Description

MULTIMAX MP 519 est un pneu particulièrement conçu pour les camions légers dans toutes les applications de transport. La carcasse renforcée avec ceintures d'acier garantit une excellente stabilité et une vitesse élevée (90 km/h). Grâce à la faible résistance au roulement, le pneu assure une consommation réduite de carburant.

UM

International Standard

Construction

 RADIAL

Machinery

Industriel: Camion léger

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
7.50 R 16 LT	STANDARD	109/107 G	6	6.00	5.50 F ; 6 L ; 7 L	220	810	377	2449	TL	
7.50 R 16 LT	STANDARD	112/110G	8	6.00	5.50 F ; 6 L ; 7 L	220	810	377	2449	TL	E11-54R-0019046

Printed on 19/04/2024 04:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..