

## MULTIMAX MP 522 - Spécifications techniques



### Description

MULTIMAX MP 522 est le pneu polyvalent de BKT conçu pour de nombreux domaines d'application dans le secteur agro-industriel. Il est adapté pour toutes les opérations de levage et chargement sur véhicules tels que les chargeurs télescopiques et chargeuses compactes. Stabilité et traction sont ses atouts, associés à une excellente résistance aux crevaisons. Grâce au mélange particulier, MULTIMAX MP 522 garantit une résistance aux coupures et déchirures exceptionnelle.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	440/80 R 28 IND
LI/SS	156 A8/B

## Dimensions US Standard

Usa code	94052240
Section Width (inch)	17.4
Overall Diameter (inch)	55.7
Static Loaded Radius (inch)	25.3
Rolling Circumference (inch)	168.4
Rim Rec	DW 14 L
Rim Alt	DW 13 ; DW 13 L ; DW 15 L
ECE	E11-106R-002968

## Load capacity (lbs)

mph / psi	23	29	32	35	38	41	44	46	49	52
30	5070	6010	6480	6940	7410	7880	8360	8820	-	-
25	5070	6010	6480	6940	7410	7880	8360	8820	-	-
20	5470	6460	6960	7450	7950	8440	8940	9440	-	-
15	5670	6700	7210	7730	8240	8750	9270	9790	-	-
5 Cyc.	6260	7650	8360	9050	9740	10440	11130	11840	12530	13230
Static	9610	11750	12810	13880	14950	16020	17080	18140	19210	20280

Printed on 14/04/2024 07:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..