

## MULTIMAX MP 522 - Fiche de données



### Description

MULTIMAX MP 522 est le pneu polyvalent de BKT conçu pour de nombreux domaines d'application dans le secteur agro-industriel. Il est adapté pour toutes les opérations de levage et chargement sur véhicules tels que les chargeurs télescopiques et chargeuses compactes. Stabilité et traction sont ses atouts, associés à une excellente résistance aux crevaisons. Grâce au mélange particulier, MULTIMAX MP 522 garantit une résistance aux coupures et déchirures exceptionnelle.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>280/80 R 18 IND</b> <b>(10.5/80 R 18)</b>	STANDARD	94045044	132 A8/B	W 9 ; 9 ; 9 SDC	W 8 ; W 10	11.1	35.7	16.6	108.2	TL	E11-106R-002962
<b>340/80 R 18 IND</b> <b>(12.5/80 R 18)</b>	STANDARD	94048793	143 A8/B	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	13.5	39.6	18	119	TL	E4-106R-002654
<b>340/80 R 20 IND</b>	STANDARD	94052875	144 A8/B	11	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC	13.5	41.4	18.9	126.5	TL	E11-106R-002969
<b>380/75 R 20 IND</b> <b>(14.5 R 20)</b>	STANDARD	94045877	148 A8/B	W 12	W 11 ; 11 ; 12	15.1	42.3	19	128	TL	E11-106R-002963
<b>400/70 R 20 IND</b> <b>(16.0/70 R 20)</b>	STANDARD	94033829	149 A8/B	13	12 SDC ; 13 SDC ; 14	15.9	42	18.7	126.9	TL	E4-106R-002319
<b>400/70 R 24 IND</b>	STANDARD	94051403	152 A8/B	13	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L	15.9	46.1	21	138.9	TL	E11-106R-002964
<b>400/80 R 24 IND</b> <b>(16.0/80 R 24)</b>	STANDARD	94051397	162 A8/B	DW 13	DW 12 ; DW 13 L ; DW 14 L	15.9	49.2	21.8	148.7	TL	E11-106R-002965
<b>440/80 R 24 IND</b>	STANDARD	94052257	161 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	17.4	51.7	23.1	155.8	TL	E11-106R-002966
<b>460/70 R 24 IND</b> <b>(17.5L R 24)</b>	STANDARD	94031313	159 A8/B	DW 15 L	DW 14 L ; DW 16 L	18.3	49.2	22.4	148.3	TL	E4-106R-002396
<b>500/70 R 24 IND</b> <b>(19.5L R 24)</b>	STANDARD	94032686	164 A8/B	DW 16 L	DW 15 L ; DW 18 L	19.8	51.6	23.4	155.1	TL	E4-106R-002395
<b>540/70 R 24 IND</b>	STANDARD	94052264	168 A8/B	DW 16 L	DW 18 L	20.9	53.8	24.1	162.7	TL	E11-106R-002967
<b>480/80 R 26 IND</b>	STANDARD	94052707	160 A8/B	DW 15 L	DW 16 L	18.9	56.2	25.1	168.8	TL	E11-106R-002970
<b>480/80 R 26 IND</b>	STANDARD	94073108	167 A8/B	DW 15 L	DW 16 L	18.9	56.2	25.1	168.8	TL	E11-106R-008146
<b>440/80 R 28 IND</b>	STANDARD	94052240	156 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	17.4	55.7	25.3	168.4	TL	E11-106R-002968

Printed on 14/04/2024 05:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..