

MULTIMAX MP 527 - Spécifications techniques



Description

MULTIMAX MP 527 est un pneu radial polyvalent pour chargeurs télescopiques et chargeuses compactes dans les applications agro-industrielles. Ce pneu présente un dessin à blocs de la bande de roulement qui garantit une excellente traction même sur les surfaces dures. Le flanc robuste du pneu assure une stabilité exceptionnelle en mode levage. MULTIMAX MP 527 est réalisé avec un mélange particulièrement résistant aux coupures et déchirures, ce qui se traduit par une longue vie du pneu.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	400/70 R 24 IND
LI/SS	152 A8/B

Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	1170
Static Loaded Radius (mm)	542
Rolling Circumference (mm)	3597
SRI (mm)	575
Rim Rec	13
Rim Alt	DW 12 ; DW 13 ; DW 13 L ; 13 SDC ; DW 14 L
ECE	E11-106R-003958

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1705	2025	2310	2630	2950	3160	3550	-	-
40	1705	2025	2310	2630	2950	3160	3550	-	-
30	1825	2170	2470	2815	3155	3385	3800	-	-
25	1895	2250	2565	2920	3275	3515	3945	-	-
10 Cyc.	2080	2560	3010	3465	3945	4290	4850	5115	5325
Static	3185	3920	4615	5310	6045	6575	7435	7840	8165

Printed on 21/04/2024 00:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..