

MULTIMAX MP 527 - Spécifications techniques



Description

MULTIMAX MP 527 est un pneu radial polyvalent pour chargeurs télescopiques et chargeuses compactes dans les applications agro-industrielles. Ce pneu présente un dessin à blocs de la bande de roulement qui garantit une excellente traction même sur les surfaces dures. Le flanc robuste du pneu assure une stabilité exceptionnelle en mode levage. MULTIMAX MP 527 est réalisé avec un mélange particulièrement résistant aux coupures et déchirures, ce qui se traduit par une longue vie du pneu.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	500/70 R 24 IND
LI/SS	164 A8/B

Dimensions US Standard

Usa code	94052233
Section Width (inch)	19.8
Overall Diameter (inch)	51.6
Static Loaded Radius (inch)	23.5
Rolling Circumference (inch)	158.2
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; DW 18 L
ECE	E4-106R-002658

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	5290	6280	7160	8160	9150	9810	11020	-	-
25	5290	6280	7160	8160	9150	9810	11020	-	-
20	5670	6720	7670	8730	9800	10500	11790	-	-
15	5870	6980	7960	9060	10160	10890	11230	-	-
5 Cyc.	6450	7940	9350	10750	12230	13320	15050	15870	16530
Static	9890	12170	14330	16480	18760	20410	23070	24340	25350

Printed on 17/04/2024 21:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..