

## MULTIMAX MP 538 - Spécifications techniques



### Description

Le MULTIMAX MP 538 est un pneu radial polyvalent spécialement conçu pour plusieurs applications et machines : les niveleuses et les chargeuses travaillant dans des conditions hivernales, ainsi que les chariots télescopiques, les véhicules universels et les balayeuses pour l'entretien des routes.

Grâce à sa robuste carcasse avec ceinture d'acier, le MULTIMAX MP 538 permet de transporter de lourdes charges y compris à grande vitesse. En outre, la conception unique de sa bande de roulement permet de maintenir une excellente traction sur la glace et la neige.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Chargeuse télescopique • Véhicule universel  
Industriel: Niveleuse • Chargeur

Version	STEEL BELTED
Type	TL
Tyre Size	405/70 R 20 MPT
LI/SS	152 G

## Dimensions US Standard

Usa code	94069682
Section Width (inch)	16
Overall Diameter (inch)	42.4
Static Loaded Radius (inch)	19.1
Rolling Circumference (inch)	129.5
Rim Rec	W13

## Load capacity (lbs)

mph / psi	87
55	7850
40	8500
25	9000

Printed on 04/03/2024 11:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..