

MULTIMAX MP 540 - Spécifications techniques



Description

Le MULTIMAX MP 540 a été conçu par BKT pour tous les véhicules polyvalents. Grâce à la carcasse tout en acier, le MULTIMAX MP 540 permet de transporter de lourdes charges sur route et hors route. De plus, sa conception de sculpture en bloc offre une stabilité et une durabilité exceptionnelles.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule universel

Industriel: Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	365/80 R 20 (14.5 R 20)
LI/SS	152 K

Dimensions International Standard

Overall Width (mm)	365
Overall Diameter (mm)	1086
Static Loaded Radius (mm)	495
Rolling Circumference (mm)	3308
Rim Rec	11
ECE	E11-54R-0020145

Load capacity (Kg)

km/h / bar	6.25
110	3550

Printed on 14/04/2024 04:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..