

MULTIMAX MP 569 - Spécifications techniques



Description

Le nouveau pneu MULTIMAX MP 569 est spécialement conçu pour les camions agricoles. Il s'agit d'une solution innovante qui améliore tant les performances du tracteur que du camion pour répondre aux besoins spécifiques de l'agriculture moderne dans différentes applications. Grâce à sa carcasse tout acier, le pneu se distingue par son rendement à des vitesses élevées et par sa durabilité. La sculpture optimisée de la bande de roulement offre une traction accrue sur le terrain et des propriétés autonettoyantes exceptionnelles, ainsi qu'une conduite extrêmement confortable sur la route et une excellente stabilité. Sans oublier que MULTIMAX MP 569 permet de réaliser des économies significatives en matière de consommation de carburant grâce à une faible résistance au roulement.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Chargeuse télescopique • Camions agricole
Industriel: Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	445/65 R 22.5 (18 R 22.5)
LI/SS	169 J

Dimensions International Standard

Overall Width (mm)	440
Overall Diameter (mm)	1174
Static Loaded Radius (mm)	528
Rolling Circumference (mm)	3558
Rim Rec	13.00
Rim Alt	14.00
ECE	E11-54R-0019094

Load capacity (Kg)

km/h / bar	9.00
100	5800

Printed on 27/04/2024 09:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..