

PAC MASTER - Spécifications techniques



Description

PAC MASTER est un pneu diagonal pour compacteurs. Il offre une grande stabilité et assure un cycle de vie plus long. Ce pneu est réalisé dans un mélange spécial qui lui confère une résistance particulière à la chaleur.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Compacteur

| | |
|-----------|------------|
| Version | SPECIAL |
| Type | TT |
| Tyre Size | 11.00 - 20 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94067169 |
| Ply Rating | 18 |
| Section Width (inch) | 11.5 |
| Overall Diameter (inch) | 42.1 |
| Static Loaded Radius (inch) | 19.4 |
| Rolling Circumference (inch) | 130.3 |
| Rim Rec | 8.0 |
| Rim Alt | 8.5 |
| ECE | E11-106R-006177 |

Load capacity (lbs)

| mph / psi | 120 |
|-----------|-------|
| 5 | 12800 |
| 10 | 10200 |

Printed on 25/04/2024 16:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..