

PAC MASTER - Spécifications techniques



Description

PAC MASTER est un pneu diagonal pour compacteurs. Il offre une grande stabilité et assure un cycle de vie plus long. Ce pneu est réalisé dans un mélange spécial qui lui confère une résistance particulière à la chaleur.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Compacteur

Version	STANDARD
Type	TL
Tyre Size	190/60 - 15

Dimensions International Standard

Ply Rating	6
Section Width (mm)	186
Overall Diameter (mm)	610
Static Loaded Radius (mm)	291
Rolling Circumference (mm)	1853
Rim Rec	6.0
ECE	E11-106R-005272

Load capacity (Kg)

	km/h / bar	2.80
	10	750
	15	600

Printed on 25/04/2024 18:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..