

PL 801 - Spécifications techniques



Description

PL 801 a été particulièrement conçu pour des applications avec andaineurs rotatifs/faneuses et pour les opérations de logistique avec chariots élévateurs. Ce pneu offre une excellente stabilité en même temps qu'une grande résistance à tout type de coupure. PL 801 assure un cycle de vie plus long du pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Moissonneuse • Adaineur rotatif • Chariot élévateur

Industriel: Chariot élévateur

Version	STANDARD
Type	TT
Tyre Size	250 - 15 (250/70 - 15)

Dimensions US Standard

Usa code	94007059
Ply Rating	16
Section Width (inch)	9.3
Overall Diameter (inch)	29.3
Rim Rec	7.50 BD
Rim Alt	7.0 ; 7.5

Load capacity (lbs)

mph / psi	120
15 LOAD WHEEL	9600
15 STEER WHEEL	7385
5 OTHER VEHICLES	9600
15 OTHER VEHICLES	7385
STATIC SIDE LOADER	11155

Printed on 20/04/2024 15:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..