

PL 801 - Spécifications techniques



Description

PL 801 a été particulièrement conçu pour des applications avec andaineurs rotatifs/faneuses et pour les opérations de logistique avec chariots élévateurs. Ce pneu offre une excellente stabilité en même temps qu'une grande résistance à tout type de coupure. PL 801 assure un cycle de vie plus long du pneu.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Moissonneuse • Adaineur rotatif • Chariot élévateur

Industriel: Chariot élévateur

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9
LI/SS	A8 114

Dimensions International Standard

Ply Rating	10
Section Width (mm)	157
Overall Diameter (mm)	543
Rim Rec	4.00 E
ECE	E11-106R-003564

Load capacity (Kg)

	km/h / bar	8.50
25 LOAD WHEEL		1715
25 STEER WHEEL		1320
10 OTHER VEHICLES		1715
25 OTHER VEHICLES		1320
STATIC SIDE LOADER		1995

Printed on 08/12/2023 07:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..