

PL 801 - Spécifications techniques



Description

PL 801 a été particulièrement conçu pour des applications avec andaineurs rotatifs/faneuses et pour les opérations de logistique avec chariots élévateurs. Ce pneu offre une excellente stabilité en même temps qu'une grande résistance à tout type de coupure. PL 801 assure un cycle de vie plus long du pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Moissonneuse • Adaineur rotatif • Chariot élévateur

Industriel: Chariot élévateur

Version	SPECIAL
Type	TT
Tyre Size	6.00 - 9

Dimensions US Standard

Usa code	94035052
Ply Rating	10
Section Width (inch)	6.2
Overall Diameter (inch)	21.4
Rim Rec	4.00 E

Load capacity (lbs)

	mph / psi	123
15 LOAD WHEEL		3780
15 STEER WHEEL		2910
5 OTHER VEHICLES		3780
15 OTHER VEHICLES		2910
STATIC SIDE LOADER		4400

Printed on 29/01/2023 13:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..