

## PL 801 - Spécifications techniques



### Description

PL 801 a été particulièrement conçu pour des applications avec andaineurs rotatifs/faneuses et pour les opérations de logistique avec chariots élévateurs. Ce pneu offre une excellente stabilité en même temps qu'une grande résistance à tout type de coupure. PL 801 assure un cycle de vie plus long du pneu.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Moissonneuse • Adaineur rotatif • Chariot élévateur

Industriel: Chariot élévateur

Version	STANDARD
Type	TT
Tyre Size	8.15 - 15 (28 X 9 - 15)

## Dimensions US Standard

Usa code	94007271
Ply Rating	14
Section Width (inch)	8.5
Overall Diameter (inch)	28.3
Rim Rec	7.0
Rim Alt	7.00 BD
ECE	E11-106R-003631

## Load capacity (lbs)

	mph / psi	145
	15 LOAD WHEEL	8600
	15 STEER WHEEL	6615
	5 OTHER VEHICLES	8600
	15 OTHER VEHICLES	6615
	STATIC SIDE LOADER	9985

Printed on 20/04/2024 04:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..