

PL 846 - Spécifications techniques



Description

PL 846 a été particulièrement conçu pour les outils agricoles dans les applications de travail de la terre. Ce pneu offre une stabilité extraordinaire et une traction exceptionnelle, ainsi qu'une grande résistance à tout type de coupure. PL 846 est le pneu idéal pour les surfaces rocheuses.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9

Dimensions International Standard

Ply Rating	10
Section Width (mm)	160
Overall Diameter (mm)	540
Rim Rec	4.00 E

Load capacity (Kg)

km/h / bar	8.50
25	1320

Printed on 25/04/2024 22:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..