

## PORT KING CLASSIC - Spécifications techniques



### Description

Port King Classic est le pneu de port BKT de dernière génération, particulièrement étudié pour les équipements de manutention des conteneurs. Le pneu assure une efficacité opérationnelle maximale et une stabilité exceptionnelle en matière de soulèvement. Grâce à sa carcasse robuste en nylon, Port King Classic se distingue par sa capacité de charge plus élevée, en minimisant le risque de ruptures, lacérations et coupures. Le nouveau mélange résistant à l'usure a été développé pour assurer un cycle de vie prolongé du produit ainsi qu'un meilleur rendement sur l'investissement.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriel: Reach stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

## Dimensions International Standard

Ply Rating	40
Overall Width (mm)	528
Overall Diameter (mm)	1675
Static Loaded Radius (mm)	765
Rolling Circumference (mm)	4955
Rim Rec	13.00 /2.5
Rim Alt	15.00/2.5
TRA Code	IND4

## Load capacity (Kg)

km/h / bar	10.00
10	22950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/02/2025 05:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..