

## POWER RIB F2 - Spécifications techniques



### Description

POWER RIB F2 a été particulièrement conçu pour les tracteurs 2WD/2RM dans les applications de travail de la terre. Ce pneu, qui trouve son utilisation essentiellement aux champs, est parfait pour toutes les opérations qui demandent un excellent braquage.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Tracteur 2WD

Version	STANDARD
Type	TL
Tyre Size	11L - 15 SL
LI/SS	106 A8

## Dimensions US Standard

Usa code	94020430
Ply Rating	8
Section Width (inch)	11
Overall Diameter (inch)	32
Static Loaded Radius (inch)	14.7
Rolling Circumference (inch)	95.4
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-004652
TRA Code	F2

## Load capacity (lbs)

mph / psi	44
25	2090

Printed on 26/04/2024 09:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..