

POWER TRAX HD SMOOTH - Spécifications techniques



Description

POWER TRAX HD SMOOTH est un pneu à construction diagonale spécialement conçu pour les opérations dans les ports et les mines souterraines. La protection particulière du flanc et la bande de roulement pleine préviennent les dommages dus aux coupures et crevaisons qui sont fréquents dans ces milieux difficiles. Si vous avez besoin de déplacer de lourdes charges, Power Trax HD Smooth est le pneu idéal pour répondre à vos exigences.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneur • Chariot élévateur
OTR: Véhicule miniers souterrains

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions US Standard

Usa code	94007882
Ply Rating	20
Section Width (inch)	12.6
Overall Diameter (inch)	45.3
Rim Rec	8.50
Rim Alt	9.0
ECE	E11-106R-005561

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	20350
15 STEER WHEEL	15650
5 OTHER VEHICLES	20350
15 OTHER VEHICLES	15650
STATIC SIDE LOADER	23630

Printed on 25/04/2024 18:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..