

POWER TRAX HD SMOOTH - Fiche de données



Description

POWER TRAX HD SMOOTH est un pneu à construction diagonale spécialement conçu pour les opérations dans les ports et les mines souterraines. La protection particulière du flanc et la bande de roulement pleine préviennent les dommages dus aux coupures et crevaisons qui sont fréquents dans ces milieux difficiles. Si vous avez besoin de déplacer de lourdes charges, Power Trax HD Smooth est le pneu idéal pour répondre à vos exigences.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneur • Chariot élévateur
OTR: Véhicule miniers souterrains

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
12.00 - 20	STANDARD	94007882	20	8.50	9.0	12.6	45.3	TT	E11-106R-005561
12.00 - 20	STANDARD	94062997	28	8.50	9.0	12.6	45.3	TT	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 21:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..