

## POWER TRAX HD (SS) - Spécifications techniques



### Description

Le pneu POWER TRAX HD premium est spécialement conçu pour les équipements dans les ports et les mines souterraines. Sa bande de roulement profonde, son côté extra-épais et sa carcasse résistante lui confèrent une durabilité exceptionnelle, minimisant les risques de crevaison et de dommages accidentels. Le pneu présente une excellente résistance aux coupures et aux éclats, ce qui le rend particulièrement adapté aux surfaces rugueuses et dures. Le protège-jante de conception spécifique assure une protection contre les crevaisons et les impacts et chocs au niveau du rebord de la jante.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriel: Chargeur compact

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

## Dimensions US Standard

Usa code	94017300
Ply Rating	10
Section Width (inch)	10.6
Overall Diameter (inch)	31.1
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	91.8
Rim Rec	8.25

ECE

## Load capacity (lbs)

mph / psi	75
5	4710
10	3710
15	3440

Printed on 23/04/2024 13:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..