

## POWERTRAILER SR 331 - Spécifications techniques



### Description

Le POWERTRAILER SR 331 est le tout nouveau pneu radial All Steel (Tout Acier) de BKT, spécialement conçu pour les remorques et les camions-citernes dans les applications de transport. Développé pour une utilisation sur le terrain et sur la route, le POWERTRAILER SR 331 se distingue par ses bonnes propriétés de flottaison dans les champs ainsi que par son excellente traction sur l'asphalte ou d'autres surfaces dures et améliorées. La construction All Steel est synonyme de capacité de charge élevée, de stabilité extraordinaire de la carcasse et d'une durabilité prolongée du pneu. La nervure spéciale du flanc offre une protection exceptionnelle contre les chocs et les effets du frottement du pneu, tandis que le talon hexagonal renforcé avec bandelette garantit que le pneu s'adapte parfaitement à la jante. En outre, la bande de roulement multiblocs garantit une résistance au roulement réduite, une pression de contact uniforme et une bonne tenue de route. Grâce à toutes ces caractéristiques, POWERTRAILER SR 331 est synonyme d'économie de carburant et de confort routier.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Véhicule citerne • Remorque

Version	IMPLEMENT
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	169 D

## Dimensions International Standard

Overall Width (mm)	555
Overall Diameter (mm)	1245
Static Loaded Radius (mm)	565
Rolling Circumference (mm)	3775
SRI (mm)	600
Rim Rec	AG 16.00
Rim Alt	17.00 ; AG18.00
ECE	E11-106R-0010147

## Load capacity (Kg)

km/h / bar	3.2	3.6	4	4.5	5	5.5	6
10	6785	7410	8145	8665	9185	9815	10440
25	5955	6505	7150	7605	8065	8615	9165
40	5125	5600	6155	6545	6940	7415	7890
50	4560	4985	5475	5825	6175	6595	7020
65	3770	4118	4524	4814	5104	5452	5800
70	3430	3745	4115	4380	4645	4960	5280

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/02/2025 11:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..