

PUDDLE SPECIAL (A) - Spécifications techniques



Description

PUDDLE SPECIAL est un pneu pour l'agriculture R-2 particulièrement conçu pour les applications dans les rizières. Le dessin extra-profond de la bande de roulement, en plus de la disposition spéciale des pavés, assure une adhérence parfaite et une excellente traction même sur terrains meubles et mouillés. Le large élément central offre une meilleure capacité d'adaptation pour les applications sur route ainsi que d'excellentes performances opérationnelles. Qui plus est, PUDDLE SPECIAL bénéficie d'excellentes capacités d'auto-nettoyage et d'une durabilité élevée.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	12.4 - 28
LI/SS	137 A2

Dimensions International Standard

Ply Rating	12
Section Width (mm)	325
Overall Diameter (mm)	1385
Static Loaded Radius (mm)	649
Rolling Circumference (mm)	4067
Rim Rec	W 11
Rim Alt	W 10
TRA Code	R2+

Load capacity (Kg)

km/h / bar	3.50
10	2300

Printed on 19/04/2024 15:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..