

## RIB 774 (A) - Spécifications techniques



### Description

RIB 774 (A) est un pneu à taille basse qui offre une capacité de charge élevée ainsi qu'un long cycle de vie. Ce pneu est idéal pour les applications de récolte du foin et de transport avec presses à paille e remorques.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Moissonneuse • Remorque

Version	STANDARD
Type	TL
Tyre Size	18 X 8.50 - 8
LI/SS FREE ROLLING	85 A8

## Dimensions US Standard

Usa code	94056910
Ply Rating	6
Section Width (inch)	8.9
Overall Diameter (inch)	18.1
Static Loaded Radius (inch)	8.5
Rolling Circumference (inch)	54.7
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-004622

## Load capacity (lbs)

mph / psi	44
5 FR	1590
15 FR	1360
20 FR	1270
25 FR	1140

Printed on 26/04/2024 08:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..