

## RIB 774 (A) - Spécifications techniques



### Description

RIB 774 (A) est un pneu à taille basse qui offre une capacité de charge élevée ainsi qu'un long cycle de vie. Ce pneu est idéal pour les applications de récolte du foin et de transport avec presses à paille e remorques.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Moissonneuse • Remorque

Version	STANDARD
Type	TT
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	106 A8

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	210
Overall Diameter (mm)	610
Static Loaded Radius (mm)	288
Rolling Circumference (mm)	1888
Rim Rec	AG 6.75
ECE	E4-106R-002664

## Load capacity (Kg)

	km/h / bar	5.00
	10 FR	1330
	25 FR	1130
	30 FR	1065
	40 FR	950

Printed on 26/04/2024 10:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..