

RIB 774 (B) - Spécifications techniques



Description

RIB 774 (B) est un pneu à taille basse pour outils agricoles, idéal pour l'agriculture moderne. Ce pneu convient aussi bien pour les applications sur route que hors route avec les outils agricoles et les remorques. Ce pneu offre une grande capacité de charge ainsi qu'un long cycle de vie. Une version « HD » est disponible pour les opérations pénibles.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Remorque
Industriel: Remorque

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	141 A8

Dimensions US Standard

Usa code	94010967
Ply Rating	14
Section Width (inch)	15.4
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	98
Rim Rec	13.00
Rim Alt	13
ECE	E11-106R-004311

Load capacity (lbs)

mph / psi	54
5 FR	7950
15 FR	6760
20 FR	6360
25 FR	5680

Printed on 27/04/2024 04:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..