

RIB 774 (C) - Fiche de données



Description

RIB 774 (C) est un pneu à taille basse avec base étroite pour outils agricoles, idéal pour les applications de récolte du foin et de transport avec presses à paille e remorques. Ce pneu offre une grande capacité de charge ainsi qu'un long cycle de vie sur route que hors route.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Remorque

SIZE	Version	USACode	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
19.0/45 - 17	STANDARD	94027330	138 A8	10	16.00		17.9	33.3	15.2	99.1	TL	E11-106R-004589
215/75 - 17.5	STANDARD	94011001	134 A8	12	6.75		8.7	30.5	14.2	90.9	TL	E11-106R-004590
215/75 - 17.5	STANDARD	94038084	139 A8	16	6.75		8.7	30.5	14.2	90.9	TL	E4-54R-0015341
225/75 - 17.5	STANDARD	94011025	134 A8	12	6.75		8.7	30.5	14.2	90.9	TL	E11-106R-004657
225/75 - 17.5	STANDARD	94011032	139 A8	16	6.75		8.7	30.5	14.2	90.9	TL	E11-106R-004591

Printed on 23/04/2024 16:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..