

RIB F3 - Spécifications techniques



Description

RIB F3 est un pneu pour une utilisation essentiellement aux champs avec des tracteurs 2WD/2 RM dans les opérations de travail de la terre et de transport. Certaines tailles conviennent pour les applications de transport avec outils agricoles et remorques. RIB F3 est le pneu idéal pour toutes les opérations qui demandent un niveau élevé de maniabilité et manœuvrabilité. Il a été développé avec un mélange dur qui assure une durabilité supérieure ainsi que résistance aux chaumes.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur 2WD • Remorque

Version	STANDARD
Type	TL
Tyre Size	9.00 - 16
LI/SS	120 A6/ 112 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	245
Overall Diameter (mm)	878
Static Loaded Radius (mm)	387
Rolling Circumference (mm)	2573
Rim Rec	W 8
Rim Alt	6.00 F ; W 7 ; W 8 L
ECE	E11-106R-004592
TRA Code	F3

Load capacity (Kg)

km/h / bar	4.70
30	1400
40	1120

Printed on 26/04/2024 05:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..