RIB F3 - Fiche de données

Description

RIB F3 est un pneu pour une utilisation essentiellement aux champs avec des tracteurs 2WD/2 RM dans les opérations de travail de la terre et de transport. Certaines tailles conviennent pour les applications de transport avec outils agricoles et remorques. RIB F3 est le pneu idéal pour toutes les opérations qui demandent un niveau élevé de maniabilité et manœuvrabilité. Il a été développé avec un mélange dur qui assure une durabilité supérieure ainsi que résistance aux chaumes.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Tracteur 2WD • Remorque

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
9.00 - 16	HD	94042227	F3	120 A6/ 112 A8	12	W 8	6.00 F ; W 7 ; W 8 L	9.6	34.6	15.2	101.3	TT	E11-106R-004658
9.00 - 16	STANDARD	94027781	F3	120 A6/ 112 A8	12	W 8	6.00 F ; W 7 ; W 8 L	9.6	34.6	15.2	101.3	TT	E11-106R-004592
9.00 - 16	STANDARD	94060016	F3	120 A6/ 112 A8	12	W 8	6.00 F ; W 7 ; W 8 L	9.6	34.6	15.2	101.3	TL	E11-106R-004592

Printed on 25/04/2024 21:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..