

## RIB IMPLEMENT (A) - Spécifications techniques



### Description

RIB IMPLEMENT (A) a été conçu pour les remorques et outils agricoles dans les applications de transport et pour le travail de la terre. Ce pneu est idéal pour les entreprises agricoles modernes et il offre des performances exceptionnelles tant sur route que hors route. RIB IMPLEMENT (A) est le bon choix pour toutes les conditions opérationnelles qui demandent un niveau élevé de maniabilité et manœuvrabilité ainsi qu'un moindre compactage du sol pour préserver les cultures.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	10.0/80 - 12
LI/SS FREE ROLLING	110 A8

## Dimensions US Standard

Usa code	94010868
Ply Rating	6
Section Width (inch)	10.4
Overall Diameter (inch)	29.4
Static Loaded Radius (inch)	13
Rolling Circumference (inch)	86.1
Rim Rec	9.00
Rim Alt	7.0
ECE	E11-106R-003533

## Load capacity (lbs)

mph / psi	33
5 FR	3270
15 FR	2780
20 FR	2610
25 FR	2340

Printed on 27/04/2024 05:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..