

RIB MASTER - Spécifications techniques



Description

RIB MASTER est adapté pour les opérations de transport et le travail de la terre avec des remorques, des presses à paille et les outils agricoles. Ce pneu offre une grande capacité de charge ainsi qu'un long cycle de vie.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	215/75 - 17.5
LI/SS FREE ROLLING	142 A8

Dimensions US Standard

Usa code	94010905
Ply Rating	16
Section Width (inch)	8.7
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	90.9
Rim Rec	6.75
ECE	E11-106R-004593

Load capacity (lbs)

mph / psi	131
5 FR	8130
15 FR	6960
20 FR	6550
25 FR	5840

Printed on 24/04/2024 18:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..